



- 👍 Save Cost / Save Labour
- 👍 Eco Friendly
- 👍 Save Time / High Productivity
- 👍 Excellent Bond And Adhesion Strength
- 👍 Simple Application
- 👍 Excellent Finishing

We provide a solution during construction to prevent wall finishing defects issues, helping customers make more with less through leaner processes. Satisfaction, peace of mind and cost saving

DESCRIPTION :

BEBOND BB3 is specifically designed water based non-toxic and non flammable homopolymer admixture agent to improved bonding and adhesion of all kind of cementitious products on various substrate.

ADVANTAGES

- Suitable for all kind of surfaces.
- High bonding, adhesion, tensile and flexural strength to unconventional plastering surfaces (withstand high vibration and movement).
- Suitable to bond various cementitious products such as plastering mortar, cement rendering, skim-coating and all cementitious screeds.
- Minimize cracks.
- Reduced shrinkage / shrink resistance (water resistance).
- Better finishing.
- Time and cost saving over conventional method.
- Excellent workability and simplicity - Apply with roller, no skilled worker needed.
- Ready to use (No dilution or stirring needed).

BE BOND BB3



EXCELLENT
ADHESION



LONG
OPEN TIME



WATER BASED
NON-TOXIC



NON
FLAMMABLE

PRODUCT DATA SHEET

Color	Light Blue
Packaging	20 litres / pail
Form	Water based liquid
Drying Time	Approximately 30 minutes
Open Time	External - 3 Days Internal - 7 Days
Toxicity	None
Fire Hazard	Non-Flammable
Shelf Life	1 year (12 Months) Dry conditions at ambient temperature
Storage	Store in protected area (5-37 celsius)
Coverage	Approximately 10-20m ² /L subject to type of substrate
Application Tool	Paint Roller

HEALTH & SAFETY

This product is non-toxic. In cases of allergic and sensitive skin contact, flush and clean with water. If severe medical reaction happened please seek for professional help.

USAGE

- Strongly recommend for interior and external plastering on various substrate.

APPLICATION PROCEDURE

- All surface must be structually sound, clean, and free from oil, grease, wax, dirt, curing compound, laitance, efflorescence and any other loose containinating materials which will inhibit proper bonding.
- Remove any soft, brittle and weakly bonded materials from surface of substrates. Painted surface must be scabbled / abraded prior to the application of the product.
- **BEBOND BB3** is a ready to use product. Do not dilute with water or any other form of liquid.
- Apply **BEBOND BB3** by using paint roller. Spraying method is not recommended.
- Apply a thin continuous unbroken and even film of **BEBOND BB3** to the treated surfaces by pressing the paint roller.
- Allow **BEBOND BB3** to dry for approximately 30 minutes. Continue with subsequence works (plastering, skim, rendering, etc). Plastering, rendering, skim coating and cement mortaring activity shall be performed within 7 days as long as it is uncontaminated and still intact to the substrates.
- Avoid permanent wet surface such as swimming pool, water feature wall, retaining walls etc.

WORK SEQUENCE



- 1 Apply a layer of **BEBOND BB3** on substrate with paint roller
- 2 Allow **BEBOND BB3** to dry for approximately 30 minutes
- 3 Proceed with plastering, skim coating or cement rendering works and done

BONDZ SOLUTION SDN. BHD. 202301026187 (1520110-D)

No 10, Jalan Bagan Nira 26/8, Seksyen 26, Hicom Industrial Estate, 40400 Shah Alam,
Selangor Darul Ehsan, Malaysia.

T. +6012-3102722 / +6012-6446126 | E. bondzsolution@outlook.com