



## Multi-purpose Polymer-based Primer Crystallisation Agent & Solutions for Concrete Shrinkage Crack

#### **DESCRIPTION:**

**BEBOND BBPRIME** is formulated as a polymer based primer best uses for surface preparation. Also, with high penetration ability. **BEBOND BBPRIME** effectively serve as a solution for water leaking issues aries from concrete shrinkage crack.

#### **ADVANTAGES**

#### For Surface Preparation

- · Effective, easy solution for dusty and powdery surface
- Excellent and high penetration into cement based surface
- · Durability UV and weather resistant, water repellent ability
- Flexibility Good in film forming and binding properties

#### For solution on concrete shrinkage crack (to terminate water leaking)

- · Effective and permanent solution for water leaking on shrinkage crack
- · Enormous time and cost saving when eliminates hustle extra work on hacking
- · Clean and simplicity solutions for applicator and contractor







WATER REPELLENT AGENT



IMMERSION SYSTEM (GLIS)





# **BEBOND BBPRIME**

#### PRODUCT DATA SHEET

| Color            | Blue, Clear  |
|------------------|--|
| Packaging        | 5, 20 litres / pail  |
| Form             | Water based liquid   |
| Drying Time      | Approximately 15 minutes                                   |
| Open Time        | 14 days  |
| Toxicity         | None   |
| Shelf Life       | 1 year ( 12 months ) Dry conditions at ambient temperature |
| Storage          | Store in protected area ( 5-37 celsius )                   |
| Coverage         | Approximately 9-13m²/L subject to type of substrate        |
| Application Tool | Paint Roller   |

### **BEBOND BBPRIME TO CRYSTALIZE SUBSTRATE**





Without BEBOND BBPRIME





After Treated WITH BEBOND BBPRIME

#### **USAGE**

#### **Prior to Tiles Installation**

- Treat powdery substance on tiles base surface (receiving adhesive surface)
- Treat Painted, skim coated and chipped surface for tiles installation

#### Prior to RC/Shear Wall Plastering

Treat on RC / Shear wall plaster surface

#### **Prior to Waterproofing membrane**

 Treat pin holes on the concrete substrate prior to waterproofing

#### Prior to application on Light weight block / cemboard surface

Treat powdery substance on light weight block / cemboard surface

#### **Solutions On Concrete Shrinkage Crack**

Immersion System for water leaking issue

 Effective and permanent solution for terminating water leaking issues on concrete shrinkage crack

#### **APPLICATION PROCEDURE**

#### FOR SURFACE PREPARATION

- Apply **BEBOND BBPRIME** with roller directly immerse on the cement based surface.
- Ready to use from opened cap, apply with paint roller.

#### FOR SOLUTIONS ON CONCRETE SHRINKAGE CRACK

- Prepare a media of immersion system, eg: Pipe Sleeve with socket or modified bucket. In reliable on the gravity pressure given from the media/equipment of immersion, resulting the time taken for BEBOND BBPRIME to fully penetrate and immerse into the concrete shrinkage crack, in order to terminate water leaking issues from concrete slab to soffit area.
- Ready to use from opened cap, pour directly into the media of immersion system.

#### **HEALTH & SAFETY**

This product is non-toxic. In cases of allergic and sensitive skin contact, flush and clean with water. If servere medical reaction happened please seek for professional help.